



BRICKFORM® Strip It™

Removes sealers and paints

PRODUCT DESCRIPTION

BRICKFORM Strip It is an environmentally sound and user safe stripper for solvent base sealers and paints. Strip It may be used on all masonry surfaces such as concrete, quarry tile, ceramic tile, terrazzo, cementitious overlays and other surfaces. Strip It is safe to use on all colored or imprinted concrete. Strip It contains no Methylene Chloride nor is it flammable. This product does not produce carcinogen hazards associated with petroleum solvents. Strip It meets 2005 California Air Resources Board V.O.C. standards (less than 50% V.O.C. by weight).

Before Any Application

1. Before applying, test Strip It in an inconspicuous area to ensure compatibility. For any questions regarding issues with existing surfaces, consult BRICKFORM Technical Department.
2. Strip It is a water-dispersible. However, it is most effective when used undiluted.

Important Note: Be careful not to walk on areas where Strip It is being applied as the product can be slippery underfoot. If you have to walk on area, wear slip-resistant footwear.

DIRECTIONS

Apply BRICKFORM Strip It using a mop or sprayer and work small areas at a time. Do not walk in areas where Strip It is on the floor, as it is slippery underfoot. Allow 15 minutes dwell time, then scrape or scrub with a floor buffer and a Zim Grit brush. Pick up or vacuum solution, then scrub with a properly diluted general purpose cleaner, followed by thorough rinsing. Surfaces may require the application of several coats to completely remove coating. Allow floor to dry before applying seal or finish.

LIMITATIONS

Do not use on resilient surfaces such as vinyl or vinyl composition tile.

COVERAGE RATE

Coverage rates may vary depending on surface porosity, texture, age and condition of the concrete, the application method, and other local conditions. Material usage is 60-100 square feet per gallon, depending on amount and type of coating.

PACKAGE SIZES

BRICKFORM Strip It is available in 5-gallon pails.

APPLICABLE STANDARDS

BRICKFORM Strip It complies with ASTM D3209-82 for freeze/thaw stability for a minimum of three cycles.

TECHNICAL DATA

Please refer to BRICKFORM Strip It MSDS for hazard-related information.

Color/Odor.....	Light straw/ citrus
Detergent Type.....	Nonionic
Solubility in Water.....	Miscible
pH	8±0.5
Surface Tension	29 dynes per centimeter
Specific Gravity	0.97 (H2O=1)
Density	8.1 pounds per gallon
Flash Point	140°F

BRICKFORM, A Division of Solomon Colors, Inc.

11061 Jersey Blvd
Rancho Cucamonga, 91730

Toll Free 1-800-483-9628

www.brickform.com